TEDSON DATASHEET | ENGLISH

Integral T1 - Casambi trailing-edge dimmer, 300 W

In-box dimmer for compatible phase-dimmable lamps and drivers. Three push-button inputs provide local operation alongside other Casambi lighting.

Technical specifications

Supply	100-277 V AC, 50/60 Hz
Dimming	Trailing edge
Load	Up to 300 W; maximum 1.36 A
Inrush current	90 A at 1 ms
Switch inputs	3; momentary or latching according to selected profile
Operating temperature	0 to +55 °C
Terminal capacity	2.5 mm^2
Dimensions (L × W × H)	52 × 42.51 × 22 mm
IP rating	IP20
Control	Casambi, Long Range supported

Function, article numbers and instructions continue on the next page.

Integral T1 - Casambi trailing-edge dimmer, 300 W

Article numbers and versions

VS-IT1-W

Application

In-box dimmer for compatible phase-dimmable lamps and drivers. Three push-button inputs provide local operation alongside other Casambi lighting.

Installation and configuration

• The rating requires compatible dimmable lamps/drivers. Check both continuous load and inrush current.

• Switch inputs use live. Configure their function and check continuous load and inrush current according to the installation manual.

Get started with Casambi

Use the Tedson illustrated guides to create a network, select the correct fixture profile and test the functions in the installation.

Tedson Casambi guides

Sources and further reading

Model documentation

Product information

This Tedson summary does not replace the full manufacturer installation instructions. Information applies to the listed models. Check the supplied version, selected profile and actual operation before handover.